

according to Commission Regulation (EU) 2020/878 as amended

Kontakt PR płyn

Creation date 22nd March 2023 Revision date 15th January 2024

Version 4.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier Kontakt PR płyn

Substance / mixture mixture

UFI S140-R0DW-C00A-WPNA

1.2. Relevant identified uses of the substance or mixture and uses advised against

Mixture's intended use

Cleaning agent.

Main intended use

PC-CLN-2 All-purpose (or multi-purpose) non-abrasive cleaners including degreasing agents

(unless otherwise specified in other subcategories of cleaning products)

Mixture uses advised against

The product should not be used in ways other than those referred in Section 1.

1.3. Details of the supplier of the safety data sheet

Manufacturer

Name or trade name AG TermoPasty Grzegorz Gąsowski Address Kolejowa 33 E, Sokoły, 18-218

Poland

 Identification number (CRN)
 200133730

 VAT Reg No
 PL9661767714

 Phone
 862741342

E-mail biuro@termopasty.pl Web address www.termopasty.pl

Competent person responsible for the safety data sheet

Name AG TermoPasty Grzegorz Gąsowski

E-mail biuro@termopasty.pl

1.4. Emergency telephone number

European emergency number: 112

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification of the mixture in accordance with Regulation (EC) No 1272/2008

The mixture is classified as dangerous.

Flam. Liq. 2, H225 Asp. Tox. 1, H304 Eye Irrit. 2, H319 STOT SE 3, H336

Most serious adverse physico-chemical effects

Highly flammable liquid and vapour.

Most serious adverse effects on human health and the environment

May be fatal if swallowed and enters airways. May cause drowsiness or dizziness. Causes serious eye irritation.

2.2. Label elements

Hazard pictogram







Signal word

Danger

Hazardous substances

Distillates (petroleum), hydrotreated light paraffinic isopropanol

Hazard statements

H225 Highly flammable liquid and vapour.



according to Commission Regulation (EU) 2020/878 as amended

Kontakt PR płyn

Creation date 22nd March 2023 Revision date 15th January 2024

Version

4.0

H304 May be fatal if swallowed and enters airways.

H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P280 Wear eye protection.

P301+P310 IF SWALLOWED: Immediately call a doctor.

P312 Call a doctor if you feel unwell.
P331 Do NOT induce vomiting.

P337+P313 If eye irritation persists: Get medical advice/attention.

P370+P378 In case of fire: Use powder extinguisher/sand/carbon dioxide to extinguish.

P403+P235 Store in a well-ventilated place. Keep cool.

Supplemental information

EUH208 Contains Benzenesulfonic acid, di-C10-14-alkyl derivs., calcium salts . May produce

an allergic reaction.

2.3. Other hazards

The mixture does not contain substances with endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605. Mixture does not contain any substance meet the criteria for PBT or vPvB in accordance with Annex XIII of Regulation (EC) No. 1907/2006 (REACH) as amended.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Mixture contains these hazardous substances and substances with the highest permissible concentration in the working environment

Identification numbers	Substance name	Content in % weight	Classification according to Regulation (EC) No 1272/2008	Note
Index: 649-468-00-3 CAS: 64742-55-8 EC: 265-158-7	Distillates (petroleum), hydrotreated light paraffinic	52-58,5	Asp. Tox. 1, H304	1, 2
Index: 603-117-00-0 CAS: 67-63-0 EC: 200-661-7 Registration number: 01-2119457558-25- XXXX	isopropanol	30-50	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336	
EC: 939-603-7 Registration number: 01-2119978241-36- XXXX	Benzenesulfonic acid, di-C10-14-alkyl derivs., calcium salts	<3,25	Skin Sens. 1B, H317 Specific concentration limit: Skin Sens. 1B, H317: C > 10 %	
CAS: 27859-58-1 EC: 248-698-8	(tetrapropenyl)succinic acid	<1,3	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Aquatic Chronic 4, H413	
CAS: 52305-09-6 EC: 257-836-6	2-(tetrapropenyl)succinic acid, monoester with propane-1,2-diol	<1,3	Aquatic Chronic 3, H412	
CAS: 128-37-0 EC: 204-881-4 Registration number: 01-2119565113-46- XXXX	2,6-Di-tert-butyl-p-cresol	<0,65	Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1)	9

Notes

Note L: The classification as a carcinogen need not apply if it can be shown that the substance contains less than 3 % DMSO extract as measured by IP 346 'Determination of polycyclic aromatics in unused lubricating base oils and asphaltene free petroleum fractions — Dimethyl sulphoxide extraction refractive index method', Institute of Petroleum, London. This note applies only to certain complex oil-derived substances in Part 3.



according to Commission Regulation (EU) 2020/878 as amended

Kontakt PR płyn

Creation date 22nd March 2023 Revision date 15th January 2024

Version

4.0

2 The use of the substance is restricted by Annex XVII of REACH Regulation

Full text of all classifications and hazard statements is given in the section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Do not perform artificial respiration without self-protection (e.g. a mask). Take care of your own safety. If any health problems are manifested or if in doubt, inform a doctor and show him information from this safety data sheet. If unconscious, put the person in the stabilized (recovery) position on his side with his head slightly bent backwards and make sure that airways are free; never induce vomiting. If the person vomits by himself, make sure that the vomit is not inhaled. In life threatening conditions first of all provide resuscitation of the affected person and ensure medical assistance. Respiratory arrest - provide artificial respiration immediately. Cardiac arrest - provide indirect cardiac massage immediately.

If inhaled

Terminate the exposure immediately; move the affected person to fresh air. Take care of your own safety, do not let the affected person walk! Beware of the contaminated clothes. Depending on the situation, call the medical rescue service and ensure medical treatment considering the frequent need of further observation for at least 24 hours.

If on skin

Remove contaminated clothes. Wash the affected area with plenty of water, lukewarm if possible. Soap, soap solution or shampoo should be used if there is no skin injury. Provide medical treatment if skin irritation persists. Rinse skin with water or shower.

If in eves

Rinse eyes immediately with a flow of running water, open the eyelids (also using force if needed); remove contact lenses immediately if worn by the affected person. Rinsing should continue at least for 10 minutes. Provide medical treatment, specialized if possible.

If swallowed

If the affected person vomits, make sure to prevent inhalation of the vomit (as there is a danger of lung damage after inhalation of these liquids in the airways also in infinitesimal amount). Ensure medical treatment considering the frequent need of further observation for at least 24 hours. Bring an original container with the label and the Safety Data Sheet of the given substance as appropriate.

4.2. Most important symptoms and effects, both acute and delayed

If inhaled

Cough, headache. May cause drowsiness or dizziness.

If on skin

Not expected.

If in eyes

Causes serious eye irritation.

If swallowed

Irritation, nausea.

4.3. Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Alcohol-resistant foam, carbon dioxide, powder, water spray jet, water mist.

Unsuitable extinguishing media

Water - full jet.

5.2. Special hazards arising from the substance or mixture

In the event of fire, carbon monoxide, carbon dioxide and other toxic gases may arise. Inhalation of hazardous degradation (pyrolysis) products may cause serious health damage.

5.3. Advice for firefighters

Self-Contained Breathing Apparatus (SCBA) with a chemical protection suit only where personal (close) contact is likely. Use a self-contained breathing apparatus and full-body protective clothing. Closed containers with the product near the fire should be cooled with water. Do not allow run-off of contaminated fire extinguishing material to enter drains or surface and ground water.



according to Commission Regulation (EU) 2020/878 as amended

Kontakt PR płyn

Creation date 22nd March 2023 Revision date 15th January 2024

4.0

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Provide sufficient ventilation. Highly flammable liquid and vapour. Remove all ignition sources. Use personal protective equipment for work. Follow the instructions in the Sections 7 and 8. Do not inhale mist/vapours/spray. Prevent contact with skin and eyes.

Version

6.2. Environmental precautions

Prevent contamination of the soil and entering surface or ground water.

6.3. Methods and material for containment and cleaning up

Spilled product should be covered with suitable (non-flammable) absorbing material (sand, diatomaceous earth, earth and other suitable absorption materials); to be contained in well closed containers and removed as per the Section 13. In the event of leakage of the substantial amount of the product, inform fire brigade and other competent bodies. After removal of the product, wash the contaminated site with plenty of water. Do not use solvents.

6.4. Reference to other sections

See the Section 7, 8 and 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Prevent formation of gases and vapours in flammable or explosive concentrations and concentrations exceeding the occupational exposure limits. The product should be used only in the areas where it is not in contact with open fire and other ignition sources. Use non-sparking tools. Use of antistatic clothes and footwear is recommended. Do not inhale mist/vapours/spray. Prevent contact with skin and eyes. No smoking. Wash hands and exposed parts of the body thoroughly after handling. Use only outdoors or in a well-ventilated area. Use personal protective equipment as per Section 8. Observe valid legal regulations on safety and health protection. Ground and bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Take action to prevent static discharges.

7.2. Conditions for safe storage, including any incompatibilities

Store in tightly closed containers in cold, dry and well ventilated areas designated for this purpose. Do not expose to sunlight. Store locked up. Keep container tightly closed. Keep cool.

Content	Packaging type	Material of package
1000 ml	jerry can	FE

The specific requirements or rules relating to the substance/mixture

Solvent vapours are heavier than air and accumulate especially near the floor where they may form an explosive mixture with the air.

7.3. Specific end use(s)

not available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

The mixture contains substances for which occupational exposure limits are set.

DNEL

Distillates (petro	Distillates (petroleum), hydrotreated light paraffinic					
Workers / consumers	Route of exposure	Value	Effect	Value determination	Source	
Consumers	Inhalation	1.2 mg/m³/24h	Chronic effects systemic	1 9	aerozol (areosol)	
Workers	Inhalation	5.4 mg/m³/8h	Chronic effects systemic		aerozol (areosol)	



according to Commission Regulation (EU) 2020/878 as amended

Kontakt PR płyn

Creation date 22nd March 2023 Revision date 15th January 2024

Version

4.0

isopropanol					
Workers / consumers	Route of exposure	Value	Effect	Value determination	Source
Workers	Inhalation	500 mg/m ³	Chronic effects systemic		
Workers	Dermal	888 mg/kg bw/day	Chronic effects systemic		
Consumers	Inhalation	89 mg/m ³	Chronic effects systemic		
Consumers	Dermal	319 mg/kg bw/day	Chronic effects systemic		
Consumers	Oral	26 mg/kg bw/day	Chronic effects systemic		

PNEC

isopropanol	isopropanol				
Route of exposure	Value	Value determination	Source		
Drinking water	140.9 mg/l				
Marine water	140.9 mg/l				
Freshwater sediment	552 mg/kg of dry substance				
Freshwater environment	552 mg/kg of dry substance				
Soil (agricultural)	28 mg/kg of dry substance				

8.2. Exposure controls

Follow the usual measures intended for health protection at work and especially for good ventilation. This can be achieved only by local suction or efficient general ventilation. If exposure limits cannot be observed in this mode, suitable protection of airways must be used. Do not eat, drink and smoke during work. Wash your hands thoroughly with water and soap after work and before breaks for a meal and rest.

Eye/face protection

Protective goggles.

Skin protection

Hand protection: Protective gloves resistant to the product. Contaminated skin should be washed thoroughly.

Respiratory protection

Mask with a filter against organic vapours in a poorly ventilated environment.

Thermal hazard

Not available.

Environmental exposure controls

Observe usual measures for protection of the environment, see Section 6.2.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state liquid
Colour yellow
Odour characteristic

Melting point/freezing point data not available
Boiling point or initial boiling point and boiling range >35 °C

Flammability Highly flammable liquid and vapour.

Lower and upper explosion limit data not available

Flash point <23 °C

Auto-ignition temperature data not available
Decomposition temperature data not available
pH non-polar/aprotic



according to Commission Regulation (EU) 2020/878 as amended

Kontakt PR płyn

Creation date 22nd March 2023 Revision date 15th January 2024

Version

4.0

Kinematic viscosity data not available Solubility in water data not available Solubility in fats data not available data not available Partition coefficient n-octanol/water (log value) data not available Vapour pressure Density and/or relative density 0.829-0.850 g/cm³ Density Relative vapour density data not available Particle characteristics data not available Form liauid

9.2. Other information

Evaporation rate data not available

SECTION 10: Stability and reactivity

10.1. Reactivity

not available

10.2. Chemical stability

The product is stable under normal conditions.

10.3. Possibility of hazardous reactions

Unknown.

10.4. Conditions to avoid

The product is stable and no degradation occurs under normal use. Protect against flames, sparks, overheating and against frost.

10.5. Incompatible materials

Protect against strong acids, bases and oxidizing agents.

10.6. Hazardous decomposition products

Not developed under normal uses. Dangerous outcomes such as carbon monoxide and carbon dioxide are formed at high temperature and in fire.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Inhalation of solvent vapors above values exceeding exposure limits for working environment may result in acute inhalation poisoning, depending on the level of concentration and exposure time. No toxicological data is available for the mixture.

Acute toxicity

not available

Distillates (petroleum), hydrotreated light paraffinic						
Route of exposure	Parameter	Value	Exposure time	Species	Sex	
Oral	LD50	>5000 mg/kg		Rat		
Dermal	LD50	>5000 mg/kg		Rabbit		
Inhalation	LC ₅₀	>5.53 mg/l		Rat		

isopropanol	isopropanol						
Route of exposure	Parameter	Value	Exposure time	Species	Sex		
Inhalation	LC50	>5 mg/l	4 hours	Rat			
Oral	LD50	>2000 mg/kg	0	Rat			
Skin	LD50	>2000 mg/kg		Rabbit			

Skin corrosion/irritation

Based on available data the classification criteria are not met.



according to Commission Regulation (EU) 2020/878 as amended

Kontakt PR płyn

Creation date 22nd March 2023

Revision date 15th January 2024 Version 4.0

Serious eye damage/irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Based on available data the classification criteria are not met.

Germ cell mutagenicity

not available

Carcinogenicity

Based on available data the classification criteria are not met.

Reproductive toxicity

Based on available data the classification criteria are not met.

Toxicity for specific target organ - single exposure

May cause drowsiness or dizziness.

Toxicity for specific target organ - repeated exposure

Based on available data the classification criteria are not met.

Aspiration hazard

May be fatal if swallowed and enters airways.

11.2. Information on other hazards

The mixture does not contain substances with endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

SECTION 12: Ecological information

12.1. Toxicity

not available

Acute toxicity

Distillates (pet	Distillates (petroleum), hydrotreated light paraffinic					
Parameter	Value	Exposure time	Species	Environment		
CE50	>10000 mg/l	48 hours	Invertebrates (Daphnia magna)			
CE50	>100 mg/l	72 hours	Algae and other aquatic plants (Pseudokirchneriella subcapitata)			
CE50	>100 mg/l	96 hours	Fish (Pimephales promelas)			

isopropanol	sopropanol					
Parameter	Value	Exposure time	Species	Environment		
LC50	>100 mg/l	48 hours	Fish (Leuciscus idus)			
EC50	>100 mg/l	48 hours	Daphnia (Daphnia magna)	9		
EC50	>100 mg/l	72 hours	Algae (Scenedesmus subspicatus)	\		



according to Commission Regulation (EU) 2020/878 as amended

Kontakt PR płyn

Creation date 22nd March 2023

Revision date 15th January 2024 Version 4.0

Chronic toxicity

Distillates (petroleum), hydrotreated light paraffinic				
Parameter	Value	Exposure time	Species	Environment
NOEL	100 mg/l	21 days	Invertebrates	
NOEL	>1000 mg/l	28 days	Fish (Oncorhynchus mykiss)	

12.2. Persistence and degradability

not available

12.3. Bioaccumulative potential

Not available.

12.4. Mobility in soil

Not available.

12.5. Results of PBT and vPvB assessment

Product does not contain any substance meeting the criteria for PBT or vPvB in accordance with the Annex XIII of Regulation (EC) No 1907/2006 (REACH) as amended.

12.6. Endocrine disrupting properties

The mixture does not contain substances with endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

12.7. Other adverse effects

Not available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Hazard of environmental contamination; dispose of the waste in accordance with the local and/or national regulations. Proceed in accordance with valid regulations on waste disposal. Any unused product and contaminated packaging should be put in labelled containers for waste collection and submitted for disposal to a person authorised for waste removal (a specialized company) that is entitled for such activity. Do not empty unused product in drainage systems. The product must not be disposed of with municipal waste. Empty containers may be used at waste incinerators to produce energy or deposited in a dump with appropriate classification. Perfectly cleaned containers can be submitted for recycling.

Waste management legislation

Directive 2008/98/EC of the European Parliament and of the Council of 19 November 2008 on waste, as amended. Decision 2000/532/EC establishing a list of wastes, as amended.

SECTION 14: Transport information

14.1. UN number or ID number

UN 1993

14.2. UN proper shipping name

FLAMMABLE LIQUID, N.O.S. (isopropyl alcohol)

14.3. Transport hazard class(es)

3 Flammable liquids

14.4. Packing group

III

14.5. Environmental hazards

not relevant

14.6. Special precautions for user

Reference in the Sections 4 to 8.

14.7. Maritime transport in bulk according to IMO instruments

not relevant





according to Commission Regulation (EU) 2020/878 as amended

Kontakt PR płyn

Creation date 22nd March 2023 Revision date 15th January 2024

Version

4.0

Additional information

Hazard identification No. UN number Classification code Safety signs 30 1993

F1



Tunnel restriction code

(D/E)

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No. 1907/2006 of the European Parliament and of the Council of 18th December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing the European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No. 793/93 and Commission Regulation (EC) No. 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, as amended. REGULATION (EC) No. 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL as amended. Commission Regulation (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

Restrictions pursuant to Annex XVII of Regulation (EC) No. 1907/2006 (REACH), as amended

Distillates (petroleum), hydrotreated light paraffinic

Restriction	Conditions of restriction
28	Without prejudice to the other parts of this Annex the following shall apply to entries 28 to 30: 1. Shall not be placed on the market, or used, — as substances,
	— as constituents of other substances, or,
	— in mixtures, for supply to the general public when the individual concentration in the substance or mixture is equal to or greater than:
	— either the relevant specific concentration limit specified in Part 3 of Annex VI to Regulation (EC) No. 1272/2008, or,
	— the relevant generic concentration limit specified in Part 3 of Annex I of Regulation (EC) No 1272/2008.
	Without prejudice to the implementation of other Community provisions relating to the classification, packaging and labelling of substances and mixtures, suppliers shall ensure before the placing on the market that the packaging of such substances and mixtures is marked visibly, legibly and indelibly as follows:
	"Restricted to professional users".
	2. By way of derogation, paragraph 1 shall not apply to: (a) medicinal or veterinary products as defined by Directive 2001/82/EC and Directive 2001/83/EC;
	(b) cosmetic products as defined by Directive 76/768/EEC; (c) the following fuels and oil products:
	 motor fuels which are covered by Directive 98/70/EC, mineral oil products intended for use as fuel in mobile or fixed combustion plants, fuels sold in closed systems (e.g. liquid gas bottles);
	(d) artists' paints covered by Regulation (EC) No 1272/2008;
	(e) the substances listed in Appendix 11, column 1, for the applications or uses listed in Appendix 11 column 2. Where a date is specified in column 2 of Appendix 11, the derogation shall apply until the said date.
	(f) devices covered by Regulation (EU) 2017/745.

15.2. Chemical safety assessment

9/11

Page

A chemical safety assessment has not been carried out (mixture).



according to Commission Regulation (EU) 2020/878 as amended

Kontakt PR płyn

Creation date 22nd March 2023 Revision date 15th January 2024

15th January 2024 Version 4.0

SECTION 16: Other information

A list of standard risk phrases used in the safety data sheet

H225 Highly flammable liquid and vapour.

May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.
 H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.
 H412 Harmful to aquatic life with long lasting effects.
 H413 May cause long lasting harmful effects to aquatic life.

Guidelines for safe handling used in the safety data sheet

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P280 Wear eye protection.

P301+P310 IF SWALLOWED: Immediately call a doctor.

P312 Call a doctor if you feel unwell.
P331 Do NOT induce vomiting.

P337+P313 If eye irritation persists: Get medical advice/attention.

P370+P378 In case of fire: Use powder extinguisher/sand/carbon dioxide to extinguish.

P403+P235 Store in a well-ventilated place. Keep cool.

A list of additional standard phrases used in the safety data sheet

EUH208 Contains Benzenesulfonic acid, di-C10-14-alkyl derivs., calcium salts . May produce

an allergic reaction.

Other important information about human health protection

The product must not be - unless specifically approved by the manufacturer/importer - used for purposes other than as per the Section 1. The user is responsible for adherence to all related health protection regulations.

Key to abbreviations and acronyms used in the safety data sheet

ADR European agreement concerning the international carriage of dangerous goods by

road

BCF Bioconcentration Factor
CAS Chemical Abstracts Service

CLP Regulation (EC) No 1272/2008 on classification, labelling and packaging of

substance and mixtures

EC Identification code for each substance listed in EINECS

EC50 Concentration of a substance when it is affected 50% of the population EINECS European Inventory of Existing Commercial Chemical Substances

EmS Emergency plan EU European Union

EuPCS European Product Categorisation System IATA International Air Transport Association

IBC International Code For The Construction And Equipment of Ships Carrying

Dangerous Chemicals

ICAO International Civil Aviation Organization
IMDG International Maritime Dangerous Goods
IMO International Maritime Organization

INCI International Nomenclature of Cosmetic Ingredients
ISO International Organization for Standardization
IUPAC International Union of Pure and Applied Chemistry

LC50 Lethal concentration of a substance in which it can be expected death of 50% of the

population

LD50 Lethal dose of a substance in which it can be expected death of 50% of the

population

log Kow Octanol-water partition coefficient

NOEL No observed effect level



according to Commission Regulation (EU) 2020/878 as amended

Kontakt PR płyn

Creation date 22nd March 2023 Revision date 15th January 2024

Version

4.0

OEL Occupational Exposure Limits

PBT Persistent, Bioaccumulative and Toxic

ppm Parts per million

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals

RID Agreement on the transport of dangerous goods by rail

UN Four-figure identification number of the substance or article taken from the UN

Model Regulations

UVCB Substances of unknown or variable composition, complex reaction products or

biological materials

VOC Volatile organic compounds

vPvB Very Persistent and very Bioaccumulative

Aquatic Acute Hazardous to the aquatic environment

Aquatic Chronic Hazardous to the aquatic environment (chronic)

Asp. Tox. Aspiration hazard Eye Irrit. Eye irritation Flam. Liq. Flammable liquid Skin Irrit. Skin irritation Skin Sens. Skin sensitization

STOT SE Specific target organ toxicity - single exposure

Training guidelines

Inform the personnel about the recommended ways of use, mandatory protective equipment, first aid and prohibited ways of handling the product.

Recommended restrictions of use

not available

Information about data sources used to compile the Safety Data Sheet

REGULATION (EC) No. 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL (REACH) as amended. REGULATION (EC) No. 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL as amended. Data from the manufacturer of the substance / mixture, if available - information from registration dossiers.

The changes (which information has been added, deleted or modified)

The version 4.0 replaces the SDS version from 22 March 2023. Changes were made in sections 1, 2 and 16.

More information

Classification procedure - calculation method.

Statement

The safety data sheet provides information aimed at ensuring safety and health protection at work and environmental protection. The provided information corresponds to the current status of knowledge and experience and complies with valid legal regulations. The information should not be understood as guaranteeing the suitability and usability of the product for a particular application.

