



UL Product iQ™



JDYX2.E300003 - Fuses, Supplemental - Component

Fuses, Supplemental - Component

E300003

Supplemental micro fuses: pigtail leads

Cat. No.	Size mm(in)	Amps (A)	Volts (V)	Interrupting Rating (A)
932	8.5 x 4 x 8 (0.33 x 0.16 x 0.31)	0.1 - 0.4	400Vac	100
		0.1 - 0.4	300Vac	100
		0.1 - 0.4	277Vac	100
		0.1 - 0.4	250Vac	100
		0.1 - 0.4	125Vac	100
		0.1 - 0.4	300Vac	50
		0.1 - 0.4	250Vac	160
		0.1 - 0.4	125Vac	160
		0.5 - 6.3	400Vac	100
		0.5 - 6.3	300Vac	100
		0.5 - 6.3	277Vac	100
		0.5 - 6.3	250Vac	100
		0.5 - 6.3	125Vac	100
		0.5 - 6.3	300Vac	50
		0.5 - 6.3	250Vac	160
		0.5 - 6.3	125Vac	160
		7 - 12	400Vac	100
		7 - 12	300Vac	100
		7 - 12	277Vac	100
		7 - 12	250Vac	100
		7 - 12	125Vac	100
		7 - 12	300Vac	50
		7 - 12	250Vac	160
		7 - 12	125Vac	160



		125 - 16	400Vac	100
		125 - 16	300Vac	100
		125 - 16	277Vac	100
		125 - 16	250Vac	100
		125 - 16	125Vac	100
		125 - 16	300Vac	50
		125 - 16	250Vac	160
		125 - 16	125Vac	160

Marking: Company name and model designation.

Last Updated on 2021-02-09

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2021 UL LLC"